



TREMOLO II

The Voodoo Lab Tremolo II is handcrafted from the finest modern and vintage components and housed in a rugged aluminum case with a heavy duty metal switch. True bypass switching is used for absolutely no loss of tone when the pedal is bypassed. These are the finest effect pedals a musician can buy. For more information about Voodoo Lab products, please visit our web site at www.voodoolab.com.

DESCRIPTION

The Voodoo Lab Tremolo is designed to provide the tone and feel of a vintage tube amp tremolo. This is accomplished by using the proper waveform in conjunction with the same lamp and photocell assembly used in many popular vintage amps.

OPERATION

We've added two new controls to our Tremolo for even greater versatility. Depending on how you've set the controls you can get a perceived level change from the Tremolo. The **Volume** control is an output level trim which allows you to correct this to your desired playing volume. The **Slope** control varies the shape of the tremolo waveform. Set the slope all the way down for traditional tremolo. As you increase the slope, the rise and fall becomes sharper. When you turn it all the way up the "off" attenuation is increased for a better stutter sound. Here are some possible settings:

Shimmer: set the intensity around 3:00 and the speed nearly all the way up.

Surf: try the intensity around 2:00 and the speed around 3:00.

Leslie: turn the intensity all the way up and set the speed to the desired tempo, probably between 12:00 and 2:00.

Stutter: turn the slope all the way up. Set the intensity all the way up and the speed as desired.

Plugging into the input jack turns on the power to your Sparkle Drive. To preserve battery life, always disconnect the input cable when not in use.

Battery

The Voodoo Lab Tremolo is powered by a single 9V battery. To replace the battery, remove the four screws which secure the bottom cover.

External Power

The Voodoo Lab Tremolo can be powered externally with a regulated 9VDC power supply eliminating the need for the internal battery. The external power supply connector is a 5.5x2.1mm barrel with center negative.

WARRANTY (North America Only)

Voodoo Lab warrants this product against defects that are due to faulty material or workmanship for a period of five years from the date of original retail purchase. This warranty does not include damage to the product resulting from accident or misuse. This warranty is given to the original purchaser only and it is not assignable to any other person.

If the product should become defective within the warranty period, Voodoo Lab will repair it or replace it free of charge, provided it is returned freight prepaid to Voodoo Lab with a valid RMA (return material authorization) number.

This warranty shall not apply to any goods that have been repaired or altered by anyone other than the manufacturer. There are no warranties which extend beyond the terms described herein. Should you experience any difficulty with this Voodoo Lab product, contact us as described below. If it is determined that the product must be returned to the factory for repair, you will be issued an RMA and given shipping and packaging instructions.

Outside North America

Regions outside North American please contact your country's distributor for warranty information.

HOW TO REACH US

Tel: 707 545 0600

Email: info@voodoolab.com

Copyright ©1998-2026 by Digital Music Corp. This publication is protected by copyright and all rights are reserved. Voodoo Lab is a registered trademark of Digital Music Corp.